

SICO 1800 Dual-Height Stage



The **Dual-Height / Single Height 1800 series** offers all the advantages of a mobile folding stage, plus the added simplicity and speed of built-in height adjustability.

Mobile:

- Each section of a SICO 1800 mobile folding stage rolls freely on its own four casters. No heavy sections to lift and carry, no trucks to bother with.

Single Person Set-up:

- Designed to be set-up and taken down by one person resulting in considerable savings in labor and time.

Stores in Less Space:

- 6' x 8' (1829mm x 2439mm) stages mean fewer units needed for set-up and less storage space.

Flexible:

- Ideal for Performance Stage, Head Table Riser, Theatre-in-the-Round, Speaker's Platform, Runway, and Choral Risers.

Choose Your Deck Surface:

- Reversible decks offer a long wearing carpet surface or a scratch resistant Tuff-Deck smooth surface.

Accessories:

- Adjustable step units, ADA ramps, guard rail covers, and drapes (see pages 10 & 11).

Guard Rails

- This added safety feature must be used with all SICO stages and risers.



SICO 1800 Dual-Height Stage

Specifications:

CARPET	TUFF-DECK
1812-624	1882-624: 6' x 8' x 16" - 24" stage (183cm x 244cm x 41cm - 61cm)
1812-632	1882-632: 6' x 8' x 24" - 32" stage (183cm x 244cm x 61cm - 81cm)
1812-640	1882-640: 6' x 8' x 32" - 40" stage (183cm x 244cm x 81cm - 102cm)
1812-424	1882-424: 4' x 8' x 16" - 24" stage (122cm x 244cm x 41cm - 61cm)
1812-432	1882-432: 4' x 8' x 24" - 32" stage (122cm x 244cm x 61cm - 81cm)
1812-440	1882-440: 4' x 8' x 32" - 40" stage (122cm x 244cm x 81cm - 102cm)

SICO offers free space analysis drawings, which will provide accurate layouts for your venue with the appropriate number of stages and stage accessories.

**Single height stages available.
Call your SICO representative for details.**

SICO Tri-Height Stage

Three Height adjustments for more flexibility. Set-up at single level for meeting room stages, fashion runways, or head table settings. Set-up tiered configurations for seating or choral risers.

Easy to set-up and take-down:

- Each section rolls in on its own casters and is quickly and easily set into place. The wheels lower automatically and engage to the floor as the unit is folded for storage.

Easy to put together:

- The stage sections lock positively together with unit-to-unit connectors when units are at the same or varying heights. No cords, velcro, or tape are necessary to hold stages in place.

Easy to operate:

- Requires minimal effort to set-up, keeping staffing requirements and labor costs to a minimum.

Easy to Adjust:

- Changing heights is simple with the SICO lock and pin mechanism. Just rotate the yellow handle and adjust to the desired height. Adjusts in 6" (15 cm) increments, adhering to ADA (Americans with Disabilities Act) requirements.

Easy to Change:

- Reversible decks offer a long wearing carpet surface or a scratch resistant Tuff-Deck smooth surface.

Accessories:

- Adjustable step units, ADA ramps, guard rail covers, backdrops and drapes (see pages 10 & 11).

Guard Rails

- This added safety feature must be used with all SICO stages and risers.



All units are fully mobile, with each riding on 5" (13 cm) rubber casters. Four swivel casters allow for easier handling in and out of storage.



SICO Tri-Height Stage Specifications:

- S3H316C??41B: 6'x8'-12"/18" (305/457 mm)
- S3H316E??41B: 6'x8'-18"/24"/30" (457/610/762 mm)
- S3H316F??41B: 6'x8'- 24"/30"/36" (610/762/914 mm)
- S3H316G??41B: 6'x8'-30"/36"/42" (762/914/1067 mm)

- S3H314C??41B: 4'x8'-12"/18" (305/457 mm)
- S3H314E??41B: 4'x8'-18"/24"/30" (457/610/762 mm)
- S3H314F??41B: 4'x8'- 24"/30"/36" (610/762/914 mm)
- S3H314G??41B: 4'x8'-30"/36"/42" (762/914/1067 mm)

Decks nest firmly within the frames, spreading out the load rather than concentrating it in small areas.

SICO X-Press® Stage & Riser

The Sico X-Press® is a stage and riser system designed to meet a facility's ever-changing needs. The X-Press® converts easily from one application to another without the necessity of lifting heavy folding leg units.

- The Sico deck is structural, light-weight, and quiet. These features are made possible by a special resin impregnated honeycomb core, a solid edge, and complimented by our standard "Tuff-Deck" or carpeted surface.
- The Sico X-Press® will support 125 lbs. (57kg) per sq. ft. and a sway load of 10% or 200 lbs (91kg.) per sq. ft. uniform vertical load.
- The 4' x 8' (122cm x 244cm) lightweight frame weighs only 67 lbs. (30 kg.).
- The 3' x 8' (92cm x 243cm) deck weighs only 70 lbs. (32 kg) and the 4'x 8' (122cm x 244cm) deck weighs only 92 lbs. (42 kg).
- Availability in a variety of heights.
- Accessories: Adjustable step units, ADA ramps, guard rails, guard rail covers, and drapes.



Easy to store and transport: Caddies are available which hold up to 8 decks and frames, or 256 sq. ft. (24 sq.M) of staging.

Model # Decks	Description: Decks	Model # Frames	Description: Frames
SND144401	4' x 8" Tuff-Deck / Non-reversible (122cm - 244cm)	SNM124AB	4' x 8' / 6" high * (122cm - 244cm)
SND144XXX	4' x 8" Carpet / Non-reversible (122cm - 244cm)	SNM124BB	4' x 8' / 12" high (122cm - 244cm)
SND144XXXR	4' x 8" Tuff-Deck/Carpet Reversible (122cm - 244cm)	SNM124CB	4' x 8' / 18" - 24" high (122cm - 244cm)
SND143401	3' x 8" Tuff-Deck / Non-reversible (91cm x 244cm)	SNM124DB	4' x 8' / 24"-30"-36" high (122cm - 244cm)
SND143XXX	3' x 8" Carpet / Non-reversible (91cm x 244cm)	SNM123AB	3' x 8' / 6" high * (91cm x 244cm)
SND143XXXR	3' x 8" Tuff-Deck/Carpet (91cm x 244cm)	SNM123BB	3' x 8' / 12" high (91cm x 244cm)
SAX11FXXX	4' x 4' Corner-Section / Floor Standing (122cm - 122cm)	SNM123CB	3' x 8' / 18" - 24" high (91cm x 244cm)
SAX11SXXX	4' x 4' Corner-Section / Stage Mounted (122cm - 122cm)	SNM123DB	3' x 8' / 24"-30"-36" high (91cm x 244cm)

- **Option:** Choose between a standard black "Tuff Deck" surface, or a choice of carpet colors. Single sided or reversible.

- The Sico deck is set in place and is easily, and positively, secured to the frame.

SICO EXCLUSIVE! Expanding rubber gasket at the base of each flex pin allows decks to be secured to the frames.

- Frames are constructed of 14 gauge steel tubing for long-lasting use.

Easy height adjustment.

- **Easy to secure:** Deck sections lock together with snap-action locks. Each snap-action lock has two positions that can accommodate a stage or riser set-up.

- **Easy to adjust:** Heights are easily set with adjustable pull pins.

